

# PET IRON WHITE MATT

## 0,18mm

### PRODUCT INFORMATION BULLETIN

- For use in thermal and piezo inkjet printers
- Solvent,Eco-Solvent ,Latex and UV curable inks

#### MATERIAL DESCRIPTION

Is an extremely cost-effective and conformable magnetic receptive file with a printable surface, positionable, grey micron-iron layer.(Removable )

Great handling provides just the right amount of rigidity with no adhesive.

Easy installation - slideable and repositionable with magnetic to eliminate air bubbles.

Excellent finish, no edge lifting, shrinking or cracking  
Rust - proof

No seams splice the graphics with invisible patchwork

Compatible with all printing method

Value-Priced option

#### QUALIFICATIONS

- White Matt PET
- Top coated
- Antirust steel coating
- Easy to apply Up to 1626 mm
- Scissor cutting, knife cutting , die-cutting, and slitting can be done ease

#### INDOOR

This material is suitable for indoor displays.

No lamination is required , this mean a convenient and low cost method of producing indoor displays.

( It is difficult or impossible to remove dirt of stain from the surface , lamination will protect the material )

#### OUTDOOR

This material is suitable for outdoor displays.

For total waterproof protection always use a suitable lamination.

#### SPECIFICATIONS

Quality		White matt PET Iron
Weight		340 g/m <sup>2</sup>
Total Thickness		0,18 mm
Print side		White Matt
Whiteness	( 80,90)	
Lifting weight		3,5 g/m <sup>2</sup>
Reverse side		Brown
Tensile Strength	(MPa)	(60,75) (50,60)
Holding strenght	0,7mm	40g/cm <sup>2</sup>

## APPLICATIONS



- Wall coverage
- Pillar Graphics
- Promotional POP
- POS
- Eye catching advertisement
- Presentations
- Commercial Signage  
Safety sign  
Indoor display

## COMPATIBILITY



HP, EPSON, MUTOH, MIMAKI, ROLAND, SEIKO  
HP LATEX  
All Inkjet ( UV Curable ) printers

Max. temperature ( material ) should not exceed 55° as overheating can impair the flatness of the media. ink restrictions and heater setting have to be set for specific printer ink combinations to obtain the best result.

## GUIDELINES

### Printing

Always choose the right media for the right job. There are different kinds of inks with different kind of properties. When printing with UV stable pigment ink it's normal that the colours are different than the dye inks.

### Light stability

The light stability of a plot depends on various factors such as dye inks, UV pigmented inks and media coating but the most important factor is direct sunlight. Direct sunlight and UV will cause visible media deterioration on unprotected media within a few weeks or longer.

### Mechanical resistance

To protect the print against scratches and damage, it is recommended that media should be handled and used in a clean environment.

### Water resistance

When the plot is completely dry, the paper shows high resistance to fingerprints. Contact with water for longer period is not recommended.

### After printing

When laminating ( hot or cold ) let your prints dry 20 minutes before starting to laminate. For outdoor use, the product must have a sealed edge lamination.

### Viewing distance

Always keep in mind the minimal viewing distance, a photo paper is intended as from 30 cm distance and outdoor media 2,5 meter minimum viewing distance.

### Trouble shooting

Check that the media compatible with your printer and ink. Choose the right print mode. Check the media setting (if this

exists ) coated paper, film, etc. Perform cartridge alignment procedure if necessary. If required clean the cartridges.

### Color calibrations

As with all inkjet media , the product should be calibrated to the printer, to get the best result.

### Loading instructions

The rate which ink consumed over a given area varies between different printers and printer set-ups. This paper has excellent ink absorption capacity. When loading the media use the right set-up (mode) that gives the highest quality output.

### Printer setting and ink quantity

For optimum results, select the highest print quality. Avoid 3 colour composite black , use single colour black only.

### Shelf life and environment aspects

The shelf life of TEPEDE media is 1 year under normal conditions (10-25% at a relative humidity of 30-75%). Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place.

### Ecology

The media and the final plots can be handled and disposed of as inkjet paper media. For the treatment of ink or ink residue, please refer to your printed manual or supplier.

### Help available

If there are questions about media, just ask the TEPEDE sales department. They will inform you properly about our media program.

### Note

Specifications subject to change without notice.