

Gekko-Tex RG

PRODUCT INFORMATION BULLETIN

- For use in thermal and piezo inkjet printers.
- Latex, Solvent, UV inks.

MATERIAL DESCRIPTION



100% polyester woven fabric, treated with special inkjet coating. This product is removable self adhesive fabric, adhesives on back side so it can be adhere to any flat surface. When it is removed, there is no adhesive remain. The back side is treated with our special gray coating, it blocks back ground color so make image more vivid and colorful. Compatible with various inks and printers.

QUALIFICATIONS



- White Matt surface
- Removable adhesive
- Denier: 150D x 150D
- Back liner paper 143mic

INDOOR



The material is suitable for indoor use.

OUTDOOR



The material is not suitable for outdoor use

SPECIFICATIONS

Quality	Polyester Woven fabric
Weight	305 gsm (back liner paper 132 gsm)
Print side	White Matt
Denier	150 x 150
Thickness	339 mic (back liner paper 143 mic)
Threads per Inch	62 T
Ink Limit	250 %

APPLICATIONS



- Outdoor/Indoor signs
- Mural
- Wall advertising
- Wallpaper
- Fine-Art

COMPATIBILITY



LATEX, UV, SOLVENT, ECO-SOLVENT

GUIDELINES

Printing

Always choose the right media for the right job. There are different kinds of inks with different kind of properties. When printing with UV stable pigment ink it's normal that the colours are different that the dye inks.

Light stability

The light stability of a plot depends on various factors such as dye inks, UV pigmented inks and media coating but the most important factor is direct sunlight. Direct sunlight and UV will cause visible media deterioration on unprotected media within a few weeks or longer.

Mechanical resistance

To protect the print against scratches and damage, it is recommended that media should be handled and used in a clean enviroment.

Water resistance

When the plot is completely dry, the paper shows high resistance to fingerprints. Contact with water for longer period is not recommended.

After printing

When laminating (hot or cold) let your prints dry 20 minutes before starting to laminate. For outdoor use, the product must have a sealed edge lamination.

Viewing distance

Always keep in mind the minimal viewing distance, a photo paper is intended as from 30 cm distance and outdoor media 2,5 meter minimum viewing distance.

Trouble shooting

Check that the media compatible with your printer and ink. Choose the right print mode. Check the media setting (if this

exists) coated paper, film, etc. Perform cartridge alignment procedure if necessary. If required clean the cartridges.

Color calibrations

As with all inkjet media , the product should be calibrated to the printer, to get the best result.

Loading instructions

The rate which ink consumed over a given area varies between different printers and printer set-ups. This paper has excellent ink absorption capacity. When loading the media use the right set-up (mode) that givest the highest quality output.

Printer setting and ink quantity

For optimum results, select the highest print quality. Avoid 3 colour composite black , use single colour black only.

Shelf life and enviroment aspects

The shelf life of TEPEDE media is 1 year under normal conditions(10-25% at a relative humidity of 30-75%). Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place.

Ecology

The media and the final plots can be handled and disposed of as inkjet paper media. For the treatment of ink or ink residue, please refer to your printed manual or supplier.

Help available

If there are questions about media, just ask the TEPEDE sales department. They will inform you properly about our media program.

Note

Specifications subject to change without notice.